

SAFETY DATA SHEET

Klean-Strip Premium Sprayable Stripper

Revision: 05/01/2019

Supersedes Revision: 06/22/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Klean-Strip Premium Sprayable Stripper	
Company Name:	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100
Web site address:	www.wmbarr.com	
Emergency Contact Information:	3E 24 Hour Emergency Contact W.M. Barr Customer Service	(800)451-8346 (800)398-3892
Intended Use:	Paint/Varnish Remover	
Product Code:	GBLKSPRY, QBLK2212, GKS221, QKS2212,	
Additional Information	This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.	

2. HAZARDS IDENTIFICATION

Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 4
Acute Toxicity: Inhalation, Category 4
Skin Corrosion/Irritation, Category 1A-1C
Serious Eye Damage/Eye Irritation, Category 2A
Carcinogenicity, Category 1B
Specific Target Organ Toxicity (single exposure), Category 1



GHS Signal Word: **Danger**

GHS Hazard Phrases:

- Harmful if swallowed.
- Harmful in contact with skin.
- Causes severe skin burns and eye damage.
- Causes serious eye irritation.
- Harmful if inhaled.
- May cause cancer.
- Causes damage to organs.

GHS Precautionary Phrases:

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe gas/mist/vapors/spray.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases:

- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- IF ON SKIN: Wash with plenty of soap and water.
- IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed: Call a POISON CENTER or doctor/physician.
- IF exposed or concerned: Get medical attention/advice.

Klean-Strip Premium Sprayable Stripper

Revision: 05/01/2019

Supersedes Revision: 06/22/2017

GHS Storage and Disposal Phrases:

Immediately call a POISON CENTER or doctor/physician.
 Specific treatment see label.
 Specific measures see label.
 Rinse mouth.
 If eye irritation persists, get medical advice/attention.
 Wash contaminated clothing before reuse.

OSHA Regulatory Status:

Store locked up.
 Dispose of contents/container according to local, state and federal regulations.

Potential Health Effects (Acute and Chronic):

This material is classified as hazardous under OSHA regulations.
 This product has not been tested as a whole to determine health effects. The health effects listed below are associated with the individual ingredients listed in Section 3.

EYES: Causes eye irritation. May cause tearing, redness, stinging or burning, swelling, and blurred vision. May cause corneal injury.

SKIN: May cause effects ranging from mild irritation to severe pain, and possibly burns, depending on the intensity of contact. Skin absorption may occur.

INHALATION: May cause upper respiratory tract irritation and central nervous system depression with symptoms such as confusion, lightheadedness, dizziness, nausea, vomiting, headache, and fatigue. Causes formation of carbon monoxide in blood which may affect the cardiovascular system and central nervous system, and can cause a lack of oxygen in the blood. Continued exposure may cause unconsciousness, coma, and even death.

INGESTION: May cause nausea, vomiting, and diarrhea. May cause central nervous system excitement, followed by headache, dizziness, and drowsiness. Absorption through the gastrointestinal tract may produce central nervous system depression. May cause kidney damage. May cause blurred vision and visual impairment (including blindness).

CHRONIC OVEREXPOSURE EFFECTS: May cause liver and kidney damage. May cause cancer based on animal data (methylene chloride). Prolonged or repeated skin contact may cause defatting and dermatitis.

Methanol has caused birth defects in laboratory animals, but only when inhaled at extremely high vapor concentrations. The relevance of this finding to humans is uncertain.

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal.

ADDITIONAL DATA:

For Methylene Chloride: Alcohol may enhance the toxic effects. May cross the placenta. May be excreted in breast milk. Concurrent exposure to carbon monoxide, smoking, or physical activity may increase the level of carboxyhemoglobin in the blood resulting in additive effects.

TARGET ORGANS: blood, central nervous system, liver, skin, cardiovascular system, eyes, kidney, pancreas, heart, lungs, brain

Klean-Strip Premium Sprayable Stripper

Revision: 05/01/2019

Supersedes Revision: 06/22/2017

PRIMARY ROUTES OF ENTRY: skin, eyes, inhalation, ingestion

Medical Conditions Generally Aggravated By Exposure: Diseases of the blood, skin, eyes, liver, kidneys, lungs, cardiovascular system and respiratory system; alcoholism and rhythm disorders of the heart.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	60.0 -75.0 %
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	15.0 -25.0 %

Additional Chemical Information Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms Of Exposure:

See Potential Health Effects.

Note to Physician:

This product contains methylene chloride and methanol.

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

Methylene Chloride sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. This material is metabolized to carbon monoxide. Consequently, elevations in carboxyhemoglobin as high as 50% have been reported, and levels may continue to rise for several hours after exposure has ceased. Data in experimental animals suggest there is a narrow margin between concentrations causing anesthesia and death. Adrenalin should never be given to a person overexposed to methylene chloride.

Klean-Strip Premium Sprayable Stripper

Revision: 05/01/2019

Supersedes Revision: 06/22/2017

5. FIRE FIGHTING MEASURES

Flash Pt:	Nonflammable
Explosive Limits:	LEL: No data. UEL: No data.
Autoignition Pt:	No data.
Suitable Extinguishing Media:	Use carbon dioxide, dry powder, or foam.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	NF - Not Flammable. This material does not exhibit a flashpoint per the Setafash Closed Cup test method.
	Contact of liquid or vapor with flame or hot surfaces will produce toxic gases and a corrosive residue that will cause deterioration of metal.
Hazardous Combustion Products:	Carbon monoxide, carbon dioxide, hydrogen chloride, chlorine, phosgene

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	Isolate the immediate area. Prevent unauthorized entry. Eliminate all sources of ignition in area and downwind of the spill area. Stay upwind, out of low areas, and ventilate closed spaces before entering. All equipment used when handling this product must be grounded or non-sparking. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers. For large spills, dike ahead of the spill.
---	---

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.
Precautions To Be Taken in Storing:	Store in a cool place in original container and protect from sunlight. Exposure to high temperatures or prolonged exposure to sun may cause can to leak or swell. Once opened, remover should be used within six months or discarded to avoid can deterioration. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	ACGIH TLV	TLV: 50 ppm	
		OSHA PELs	PEL: 25 ppm STEL: 125 ppm (15 min)	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	ACGIH TLV	TLV: 200 ppm STEL: 250 ppm	
		OSHA PELs	PEL: 200 ppm	

Klean-Strip Premium Sprayable Stripper

Revision: 05/01/2019

Supersedes Revision: 06/22/2017

Respiratory Equipment (Specify Type):	<p>For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved self-contained breathing apparatus or powered air supply respirator or loose fitting hood.</p> <p>For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.</p> <p>A dust mask does not provide protection against vapors.</p>
Eye Protection:	<p>Chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.</p>
Protective Gloves:	<p>Wear gloves with as much resistance to the chemical ingredients as possible. Laminate film gloves offer the best protection. Other glove materials, such as nitrile rubber, neoprene, and PVC will be degraded by methylene chloride, but may provide protection for some amount of time, based on the type of glove and the conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.</p>
Other Protective Clothing:	<p>Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.</p>
Engineering Controls (Ventilation etc.):	<p>Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.</p> <p>Use only with adequate ventilation to prevent buildup of vapors. If the work area is not well ventilated, DO NOT use this product. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas.</p> <p>Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.</p>
Work/Hygienic/Maintenance Practices:	<p>A source of clean water should be available in the work area for flushing of the eyes and skin.</p> <p>Wash hands thoroughly after use. Do not eat, drink, or smoke in the work area.</p> <p>Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use.</p> <p>Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.</p>

Klean-Strip Premium Sprayable Stripper

Revision: 05/01/2019

Supersedes Revision: 06/22/2017

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid	
Appearance and Odor:	Translucent to colorless liquid.	
pH:	No data.	
Melting Point:	No data.	
Boiling Point:	104.00 F	
Flash Pt:	Nonflammable	
Evaporation Rate:	< 1	
Flammability (solid, gas):	No data available.	
Explosive Limits:	LEL: No data.	UEL: No data.
Vapor Pressure (vs. Air or mm Hg):	No data.	
Vapor Density (vs. Air = 1):	> 1	
Specific Gravity (Water = 1):	1.125	
Density:	9.355 LB/GL	
Solubility in Water:	Slight	
Octanol/Water Partition Coefficient:	No data.	
Percent Volatile:	98.06 % by weight.	
VOC / Volume:	24.7200 % WT	
Autoignition Pt:	No data.	
Decomposition Temperature:	No data.	
Viscosity:	350 cps	

10. STABILITY AND REACTIVITY

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	No data available.
Incompatibility - Materials To Avoid:	Bases, oxygen, sodium, potassium, strong oxidizers, reactive metals, strong acids
Hazardous Decomposition or Byproducts:	Decomposition may produce carbon monoxide and carbon dioxide, hydrogen chloride, chlorine gas, and small quantities of phosgene.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

Klean-Strip Premium Sprayable Stripper

Revision: 05/01/2019

Supersedes Revision: 06/22/2017

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole.
 CAS# 75-09-2:
 Tumorigenic Effects:, TCLo, Inhalation, Rat, 3500. PPM, 6 Y.
 Result:
 Tumorigenic: Carcinogenic by RTECS criteria.
 Endocrine: Tumors.
 - Fundamental and Applied Toxicology., Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 4,30, 1984

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.
 Result:
 Effects on Newborn: Growth statistics (e.g., reduced weight gain).
 Effects on Newborn: Physical.
 - Union Carbide Data Sheet, Union Carbide Corp., 39 Old Ridgebury Rd., Danbury, CT 06817, Vol/p/yr: 4/25, 1958

Standard Draize Test, Skin, Species: Rabbit, 810.0 MG, 24 H, Severe.
 Result:
 Specific Developmental Abnormalities: Musculoskeletal system.
 - European Journal of Toxicology and Environmental Hygiene., For publisher information, see TOERD9, Paris France, Vol/p/yr: 9,171, 1976

Chronic Toxicological Effects:

This product has not been tested as a whole.

Carcinogenicity/Other Information:

IARC 2B - Possibly Carcinogenic to Humans
 ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
 ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	Possible	2B	A3	Yes
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information:

This product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):**DOT Proper Shipping Name:** Paint Related Material**DOT Hazard Class:** 8 CORROSIVE**UN/NA Number:** UN3066**Packing Group:** II

Klean-Strip Premium Sprayable Stripper

Revision: 05/01/2019

Supersedes Revision: 06/22/2017

Additional Transport Information: The shipper/supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	No	Yes 1000 LB	Yes
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
75-09-2	Dichloromethane {Methylene chloride; R-30; Freon 30}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory, 8A CAIR CA PROP.65: Yes: Canc.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP: VHAP TSCA: Inventory CA PROP.65: Yes: RDTox.

Regulatory Information: This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

Additional Regulatory Information This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

16. OTHER INFORMATION

Revision Date: 05/01/2019
Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.